

AM 500A - Technical Specifications : Technical Specifications

RF SPECS

Output Power:**Range:**

5 W to 500 W

Accuracy:

2% full scale

Efficiency:

60% or better, 100% sinusoidal modulation of 500 W carrier into 50 Ohm load

VSWR:

Nominal 1.3:1 at full carrier power; will operate into higher VSWR with automatic power reduction, open and short circuit protected

Impedance:

50 Ohm

Frequency:**Range:**

522 kHz to 1700 kHz, supplied on one frequency (synthesized), as ordered; accommodates 9 kHz or 10 kHz channel spacing

Stability:

±3ppm, 0 to 50° C

RF Harmonics Suppression:

Meets or exceeds FCC, DOC, and CCIR requirements, when preceded by external NRSC-1 compatible audio low pass filter(s)

Modulation:**Type:**

Pulse width modulation of L+R envelope with optional integrated C-QUAM AM stereo; an RF input connector (BNC) is also provided for an external RF or stereo exciter

Capabilities:

>145% peak positive capability at rated nominal output power into 50 Ohm load

Carrier Shift:

<1% at 95% negative modulation at 1 kHz

Regulatory:

Meets or exceeds FCC and DOC technical requirements, meets ENG0215 safety requirements

AM AUDIO SPECS

Modes:

Stereo (with optional stereo card), Mono L+R, Mono L, Mono R, HD with external ASi 10; not compatible with analog stereo

Stereo (with optional stereo card):**Connector Type:**

3 position terminal block (2)

Input Level:

10 dBm, ±1 dB, L+R (or mono) to produce 100% L+R envelope modulation; other input levels accommodated by internal resistor selection

Impedance:

600 Ohm; inputs are balanced, transformerless, and resistive with passive RFI filtering; other impedances can be accommodated.

Amplitude Response:

±1 dB, 20 Hz to 10 kHz

THD + Noise:

<2.0% at 50% single channel modulation, 50 Hz to 10 kHz at rated power

S/N Radio:

>55 dB below a reference level equivalent to 100% negative modulation of either left or right channel in a 22 Hz to 30 kHz bandwidth, unweighted

Separation:

-25dB or better, 50 Hz to 10 kHz, at 50% single channel modulation into a 50 Ohm resistive load, at rated power

Squarewave Overshoot:

Broadcast Electronics

Technical Specifications

1% or less at 400 Hz, 50% single channel modulation with high frequency boost disabled

Squarewave Tilt:

1% or less at 40 Hz, 1.5% or less at 20 Hz, measured with 90% negative modulation

Incidental Phase Modulation:

Less than 2° (0.035 radians) average, or 30 dB (typical 40 dB) below equivalent 100% L-R C-QUAM modulation 50 Hz to 10 kHz, at rated power; measured with an audio input level which generates 95% negative L+R envelope modulation at 1 kHz (9.5 dBm)

Mono:

Connector Type:

3 position terminal block

Input Level:

10 dBm, ± 1 dB, L=R (or mono) to produce 100% L+R envelope modulation; other input levels accommodated by internal resistor selection

Impedance:

600 Ohm; inputs are balanced, transformerless, and resistive with passive RFI filtering; other impedances can be accommodated

Amplitude Response:

± 1 dB, 20 Hz to 10 kHz at 90% negative modulation (linear phase mode); +0.1 dB -3 dB, 20 Hz to 10 kHz at 90% negative modulation, standard configuration

THD + Noise:

<1.2%, 20 Hz to 10 kHz at rated power

Intermod Dist:

1.2% or less 1:1 ratio, 1.7% or less 4:1 ratio. 60/7000 hz SMPTE standards with 85% modulation at rated power

S/N Radio:

>65 dB below a reference level equivalent to 100% negative modulation in a 22 Hz to 30 kHz bandwidth, unweighted

Squarewave Overshoot:

0.1% or less at 400 Hz, 90% modulation (linear phase mode)

Squarewave Tilt:

1% or less at 40 Hz, less than 1.5% at 20 Hz, 90% negative modulation

MECHANICAL/PHYSICAL

Size:

Unpacked:

ECU:

19" W x 14.4" D x 10.5" H (48.0 x 36.6 x 26.7cm)

Output Network:

19" W x 27.1" D x 14" H (48.3 x 68.8 x 35.6cm)

Weight:

Unpacked:

90.6 lbs (41.1 kg)

Airflow:

Outlet Size:

ECU:

9.5" x 14" (24.1 x 35.6cm)

Output Network:

6.5" x 4.0" (16.5 x 10.2cm)

RF Output Connector:

Type N Female

ENVIRONMENTAL

Temperature:

0° to 50° C

Altitude:

10,000 ft (3,048 M) at 60 Hz; 7,500 ft (2,286 M) at 50 Hz



Broadcast Electronics

Technical Specifications

Humidity:

0% to 95% (non-condensing)

ELECTRICAL

AC Input Voltage:

196-252 VAC, 50/60Hz, single phase

Disconnect Size:

20 A

AC Wire Size:

#12 Copper AWG, THHN

Current Draw:

9.5 A max

Power Consumption:

1.25 kW at 125% sinusoidal modulation of 500 Watt carrier

Cooling Air Requirements:

250 CFM (7.08 M3/min)

Heat Dissipation:

600 Watts maximum for 500W RF output at 125% audio tone modulation

BTU:

2,000 BTU/H for 500 W RF Output at 125% audio tone modulation

Power Factor:

> 0.75 at full load

Surge Protection:

275 V MOV

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

