

FM 10T - Technical Specifications (D) : Technical Specifications

RF SPECS

Output Power:**Range:**

10 kW (4.5 kW to 11.0 kW)

Efficiency:

Typically 63% (AC line input to RF output)

VSWR:

1.8:1 maximum. (Capable of operating into higher VSWR with automatic power reduction)

Impedance:

50 ohm (others on special request)

Frequency:**Range:**

87.5 MHz to 108 MHz, tuned to specific operating frequency, exciter programmable in 10 kHz steps

Stability:

±300 Hz, 0 to 50° C

RF Harmonics Suppression:

Suppression meets all FCC/DOC requirements and CCIR recommendations

Modulation:**Type:**

Direct frequency modulation of carrier frequency

Capabilities:

Greater than ±350 kHz

Regulatory:

Meets IEC 215 safety requirements

STXE 500 EXCITER AUDIO SPECIFICATIONS

General**RF Power Output:**

40-550W

Output Impedance:

50 ohms nominal

VSWR:

Rated power into 1.5:1 VSWR. Open and short circuit protected at all phase angles

Frequency Range:

87.5MHz to 108MHz; 10kHz increments

Frequency Stability:

Internal TCXO: +/-100Hz factory calibration, +/-4ppm agin/temp, -10 degrees C to +50 degrees C; External Input: +/- accuracy of reference source

Audio Inputs:

AES, L&R analog, Unbalanced composite, SCA audio inputs, RDS input

Modulation Type:

Direct-to-channel digitally generated FM (no analog up-conversion); FM only

Modulation Capability:

Up to 300kHz

Asynchronous AM S/N Ratio:

64dB 75dB below rated power reference carrier with 100% AM modulation at 400Hz, with no FM modulation present

Synchronous AM S/N Ratio:

60dB below rated power reference carrier with 100% AM modulation at 400Hz, with FM modulation +/- 75kHz at 400Hz

Spurious and Harmonic:

Tomorrow's Radio Today

Broadcast Electronics

Technical Specifications

: 85dB or better typical, low pass filter standard

AC Input:

90 to 264VAC; 47-63Hz

Power Factor:

0.99 typical at 110VAC, 0.95 typical at 220VAC

AC Inputs Testing:

Tested to EN 301 489-1, including Voltage Dips and Dropouts (Section 9.7B), Voltage Surges (Section 9.8), and conducted immunity and conducted radiation

Regulatory:

FCC; IC; CE; BETS-6; IEC 215 Safety

Operational Modes:

Stereo, mono (L+R), L only, R only

Stereo:**Connector Type:****AES:**

Wire – XLR

L&R:

XLR

Input Level:**AES:**

-2 dBfs for 100% modulation; 16-24 bits (32, 44.1, 48 or 96 kHz typical rates for AES/EBU devices)

L&R:

+10 dBm for 100% modulation into 600 ohms

Impedance:**AES:**

110 ohm balanced

L&R:

600 ohms or 10 k selectable; balanced

Amplitude Response:**AES:**

±0.25 dB, 20 Hz to 15 kHz

L&R:

±0.25 dB, 20 Hz to 15 kHz

THD + Noise:**AES:**

0.03 or better @400Hz measured 10 Hz-22Khz, 75 uS deemphasis

L&R:

0.005 typical @400Hz, measured 10 Hz-22Khz, 75 uS deemphasis

S/N Ratio:**AES:**

95dB typical below 100% modulation @ 400Hz, 10Hz-22Khz bandwidth, A-weighted filter 100dB typical below 100% modulation @ 400 Hz, 10Hz-22Khz bandwidth, CCIR-468 filter

L&R:

86dB or better below 100% modulation @ 400Hz, 10 Hz-22Khz bandwidth, unweighted

Analog:

93dB typical below 100% modulation @ 400Hz, 10Hz-22Khz bandwidth, A-weighted filter 98dB typical below 100% modulation @ 400 Hz, 10Hz-22Khz bandwidth, CCIR-468 filter

S/N Ratio Stereo:

80dB or better below 100% modulation @ 400Hz, unweighted

Stereo Separation:

70dB or better, 20Hz to 15kHz

AES:

80 dB, 20 Hz to 15 kHz

L&R:

Broadcast Electronics

Technical Specifications

70 dB, 20 Hz to 15 kHz

Pilot Stability:

± 0.3 Hz, 0° C to +50° C

Audio Overshoot:

150% peak deviation max.

Composite Performance:

Connector Type:

BNC Unbalanced: BNC

Input Level:

3.5 V p-p for 100% modulation into 10 kOhms

Impedance:

Balanced: 10 kOhm or 50 ohm selectable, Unbalanced: 10 kOhm

Amplitude Response:

± 0.03 dB 20 Hz to 53 kHz; 0.1 dB 53 kHz to 99 kHz

Phase Response:

$\pm 0.1^\circ$ from linear phase; 53 kHz to 100 kHz

THD + Noise:

0.005% or less @ 400Hz, 10-22Khz bandwidth, 75 us deemphasis

Intermod Dist:

SMPTE: 0.01% or less (60/7000 Hz, 1:1 ratio) DIM-B: 0.005% typical (14Khz)

FM S/N Radio:

88 dB below 100% modulation @ 400 Hz, 10Hz-22Khz bandwidth, unweighted

FM S/N Ratio:

95dB typical below 100% modulation @ 400Hz, 10Hz-22Khz bandwidth, A-weighted filter

FM S/N Ratio:

100dB typical below 100% modulation @ 400 Hz, 10Hz-22Khz bandwidth, CCIR-468 filter

SCA/SCA2/RDS:

Air Conditioning Sizing:

5.41 ton A/C

Impedance:

10k ohms unbalanced

Amplitude Response:

+/- 0.1dB; 53Hz to 100kHz

19kHz Output:

19kHz synchronization clock for external RBDS/RDS operation 1V pp into high impedance

Physical:

Height:

3.5 inches (2 RU)

Width:

19" EIA rack mountable

Depth:

STXe 500 21 inches

Weight:

STXe 500 25lbs. unpacked

MECHANICAL/PHYSICAL

Size:

Unpacked:

Transmitter: 33.7" W x 37.2" D x 69.8" H (85.6 W x 94.6 D x 177.3 H cm) Power Supply: 22.7" W x 37.2" D x 69.6" H (57.6 W x 94.6 D x 177.3 H cm)

Weight:

Unpacked:



Broadcast Electronics

Technical Specifications

Transmitter: 800 lbs. (363 kg) Power Supply: 1000 lbs. (453.6 kg)

RF Output Connector:

1 5/8 inch EIA coupling or flange standard, 3 1/8 inch EIA flange optional

ENVIRONMENTAL

Temperature Range:

-10° to +50° C

Altitude:

7500 ft. (2286 M) @ 50 Hz; 10,000 ft. (3048 M) @ 60 Hz

Humidity:

0-95% Non-Condensing

ELECTRICAL

AC Input Voltage:

208/240 V Delta or WYE, 50/60 Hz, three phase. (Taps for 196 to 252 V, other voltages and line frequencies are available upon request)

Power Consumption:

Typically 15.8 kW (at 0.94 pf) at 10 kW RF output

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

