

FMi 703 - Technical Specifications : Technical Specifications

RF SPECS

Output Power:**Range:****HD Radio only:**

1 kW to 2.8 kW (-20 dB HD signal injection ratio)

FM + HD Radio:

1 kW to 7 kW (-20 dB HD signal injection ratio)

Exciter:

Broadcast Electronics FXi 60 digital FM/HD exciter

PA Efficiency:**HD Radio Only:**

40% or better at rated power

FM+HD Radio:

53% or better at rated power

Overall AC Efficiency:**HD Radio only:**

30% or better at rated power

FM + HD Radio:

45% or better at rated power

Frequency:**Range:**

87.5 MHz to 108 MHz, programmable in 10 kHz steps

Stability:

±150Hz, -10°C to +50°C using high accuracy internal oscillator. 10MHz and 1pps input for synchronization to external (GPS) reference. Automatic switching to internal oscillator if external reference fails.

VSWR:

Rated power into 1.5:1 VSWR, capable of operating in to higher VSWR with automatic power reduction, open and short circuit protected at all phase angles

RF Harmonics Suppression:

Internal harmonic filter meets or exceeds all FCC, IC, CE, CCIR and IEC215 requirements. Meets or exceeds standard NRSC-5A emission limits in all operating modes.

Modulation Type:

FM digitally synthesized direct to channel, HD digital direct to channel, FM + HD Radio digital direct to channel.

Operation Modes:

On the fly mode switching between FM only, FM + HD Radio, and HD Radio only.

FM Modulation Capability:

Great than ±300 kHz

Synchronous AM S/N Ratio:

50dB minimum below equivalent 100% amplitude modulation with 75us de-emphasis and 400Hz high pass filter (FM deviation +/- 75kHz by a 1kHz sine wave). 62dB typical below equivalent 100% amplitude modulation with 75us de-emphasis and 400Hz high pass filter (FM deviation +/- 75kHz by a 1kHz sine wave).

Asynchronous AM S/N Ratio:

55dB minimum below equivalent 100% modulation by 400Hz using 75us de-emphasis (no FM modulation present). 73dB typical below equivalent 100% modulation by 400Hz using 75us de-emphasis (no FM modulation present).

Impedance:

50 ohm

Regulatory:

Meets or exceeds all FCC requirements

AUDIO SPECIFICATIONS WITH FXI 60 DIGITAL EXCITER

Broadcast Electronics

Technical Specifications

Modes:

Stereo, mono (L+R), L only, R only; remote selectable

Stereo Performance (AES or analog inputs):

Pre-Emphasis:

Selectable None, 50 or 75 microseconds

Stereo Pilot Tone:

19kHz \pm 0.03Hz; injection level adjustable 0% to 15% in 0.1% steps; Nominal: 9%; Suppression: 38kHz, 57kHz, 76kHz, and 95kHz; 80dB below \pm 75kHz deviation.

Stereo Separation:

65dB or better, 20 to 15kHz

Dynamic Stereo Separation:

65dB or better, 20 to 15kHz

Amplitude Response:

0.1dB, 20Hz to 15kHz

Signal to Noise Ratio:

87dB or better below 100% modulation at 400Hz; measured in a 20Hz to 22kHz bandwidth with 75us de-emphasis and DIN "A" weighting.

Total Harmonic Distortion:

<.03%; 20Hz to 15kHz, in bandwidth 20Hz to 22kHz; with 75us de-emphasis

Intermodulation Distortion:

CCIF:

<.03% or less (14/15kHz 1:1)

SMPTE:

<.03% (60 and 7kHz 1:1)

Transient Intermodulation Dist:

<.03%; (2.96kHz square wave/14kHz sinewave modulation)

Linear Crosstalk:

90 dB below 100% modulation reference

Non-Linear Crosstalk:

80 dB below 100% modulation reference

Audio Overshoot:

<.2dB

Mono Performance (AES or analog input):

Pre-Emphasis:

Selectable None, 50 or 75 microseconds

FM Signal to Noise Ratio:

95dB or better below 100% modulation at 400Hz; measured in a 20Hz to 22kHz bandwidth with 75us de-emphasis and DIN "A" weighting.

Amplitude Response:

\pm .1dB, referenced to selected pre-emphasis curve.

Intermodulation Distortion:

CCIF:

.03% or less (14/15kHz 1:1)

SMPTE:

.03% or less (60/7kHz 1:1)

Transient Intermodulation Dist:

.03% or less (2.96kHz square wave/14kHz sine wave)

Composite Analog Input:

FM Signal to Noise Ratio:

95dB or better below 100% modulation at 400Hz; measured in a 20Hz to 22kHz bandwidth with 75us de-emphasis and DIN "A" weighting.

Amplitude Response:

\pm .01dB, 20Hz to 53kHz; \pm .1dB, 53kHz to 100kHz

Total Harmonic Distortion:

.005% or less over stereo sub band (10Hz to 53kHz) with 75us de-emphasis.



Intermodulation Distortion:**CCIF:**

.005% or less (14/15kHz 1:1)

SMPTE:

.005% or less (60/7kHz 1:1)

Transient Intermodulation Dist:

.005% or less (2.96kHz square wave/14kHz sine wave)

Slew Rate:

11.8V/us-symmetrical

Phase Response Variation:

$\pm 0.05^\circ$ from linear phase, 10Hz to 100kHz

Group Delay Variation:

± 5 ns, 22Hz to 53kHz, ± 30 ns, 53kHz to 100kHz.

External SCA, RBDS Performance:**SCA Format:**

Externally generated, analog FM subcarriers in the range 53-99kHz.

SCA Sub-band Amplitude Response:

± 0.5 dB; 40kHz to 100kHz.

SCA Channel FM Signal to Noise Ratio:

80dB below +6kHz subcarrier deviation at 400Hz with 150us de-emphasis.

Harmonic Distortion:

Less than .2% in audio pass-band of SCA generator

Intermodulation Distortion:

SMPTE(60 and 7kHz, 1:1): 0.2% or less, no pre/de-emphasis, SCA generator low-pass filter bypassed.

Crosstalk:**SCA to Stereo:**

80dB below 100% modulation, L or R channel with 75us de-emphasis.

Stereo to SCA:

80dB below 100% modulation referenced to ± 6 kHz deviation and 150us de-emphasis

SCA to SCA:

80dB below 100% modulation referenced to ± 6 kHz deviation and 150us de-emphasis per channel.

Dual Internal SCA Performance:**Pre-Emphasis:**

Selectable: 150us, 75us, 50us, none

Amplitude Response:

± 0.5 dB; 20Hz to 7kHz.

Subcarrier Frequency:

57kHz to 99kHz

Signal to Noise Ratio:

80dB with de-emphasis(150us).

Total Harmonic Distortion:

.1% 10Hz to 5kHz

SCA Deviation Capability:

1kHz to 10 kHz; software programmable.

Injection Level:

2% to 15%, software adjustable in 0.1% increments

Spurious & Harmonic:**2nd Harmonic:**

Better than 40dB below subcarrier

3rd Harmonic:

Better than 45dB below subcarrier

All other components:

50Hz to 100kHz: better than 80dB below subcarrier.

Broadcast Electronics

Technical Specifications

RBDS Generator (Internal):

Subcarrier Frequency:

57kHz, ± 0.1 Hz

Injection Level:

2% to 15%, software adjustable.

MECHANICAL/PHYSICAL

Size:

44.5"W x 26.5"D x 70"H (113 W x 67.3 D x 177.8 H cm)

Weight:

660 lbs (300 kg)

Heat Dissipation:

HD Radio Only:

8200 watts (28,000 BTU/Hr) @ 3500 watts RF output

FM + HD Radio:

9200 watts (31,400 BTU/Hr) @ 7500 watts RF output

RF Output Connector:

3-1/8" EIA Flange

ENVIRONMENTAL

Ambient Temperature Range:

+32°F to +122°F (0°C to 50°C)

Altitude:

To 10,000 feet (3050m) elevation above mean sea level, 60Hz operation; To 7500 feet (2286m) elevation above mean sea level, 50Hz operation

Humidity:

To 95% Non-Condensing

ELECTRICAL

AC Input Voltage:

3 Phase, Closed Delta or WYE (3 or 4 wire):

196-252 VAC, 50/60 Hz

3 Phase, 4 wire, WYE only:

340-435 VAC, 50/60 Hz

Single Phase:

196-252 VAC, 50/60 Hz

Power Factor:

.99 or better at 230 VAC

Current Draw:

3 Phase:

HD Radio Only:

25 amps

FM+HD Radio:

50 amps

Single Phase:

HD Radio Only:

43 amps

FM+HD Radio:

85 amps

AC Power Consumption:



Broadcast Electronics

Technical Specifications

HD Radio Only:

11.7 kW @ 3.5 kW RF output

FM + HD Radio:

16.7 kW @ 7.5 kW RF output

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

